



P.C.B LAYOUT
TOP VIEW



- SPECIFICATION**
- 1.Rating :DC 30V 0.5A
 - 2.Contact resistance : $\leq 0.03\Omega$
 - 3.Insulation resistance : $\geq 100M\Omega$ (DC250V)
 - 4.Withstand voltage :500VAC
 - 5.Insertion and extraction force :3–20N
 - 6.life test :5,000 cycles



HEPJ-30620	HEPJ-30620-1(H)	HEPJ-30620-M

8	AXIS SUPPORT	1	PHOSPHOR BRONZE	Au-Plating
7	CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
6	SPRING PIECE	1	SUS301	Ag-Plating
5	SPRING PIECE	1	PHOSPHOR BRONZE	Ag-Plating
4	CURVE PIECE	1	BRASS	Ag-Plating
3	CONTACT FOOT	1	SUS301	Ag-Plating
2	CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
1	HOUSING	1	PA9T Class	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X ±0.30 .XX ±0.20 .XXX ±0.10 X° ±3.0° .XX° ±2.0° .XXX° ±1.0°		UNIT:MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1	
	PHONE JACK	DESIGNER BY: Amy	2009.11.19	HEPJ-30620-X	SCALE	3:1	VER
CHECK BY: Sharon	2009.11.19	APPROVED BY: Jason	2009.11.19				1



益富科技有限公司
TEL:886-3-5511680 FAX:886-3-5511605