





Pin Number	Signal Name
1	VBUS
2	D-
3	D+
4	GND
5	StdB_SSTX-
6	StdB_SSTX+
7	GND-DRAIN
8	StdB_SSRX-
9	StdB_SSRX+

DATE	CODE	DESCRIPTION
6.0.11.2		Friday
11		Weeks
Year		
Winning		



NOTES:

*Material

Housing: PBT UL94V-0 Color:Black or Blue
Baffle : Nylon66 UL 94V-0 Rated Color:Black or Blue
Contact A(5P): Brass; Au plating on contact area,Sn(100u" min.)
plating on solder tail,Ni(50u" min.) underplating overall.
Contact B(4P): Phosphor Bronze; Au plating on contact area,
Sn(100u" min.) plating on solder tail,Ni(50u" min.)
underplating overall .
Shell: Brass; Full Ni(40u" min.) Plating.

*Mechanical

Insertion Force: 3.5Kg Max
Withdrawal Force: 1.0Kg Min
Durability: 5000 Cycles

*Electrical Specification

Current Rating: 1.8A(Only Pin1,4), 0.25A For Other Pin;
Insulation Resistance: 100MΩ Min
Contact Resistance: 30mΩ Max
Dielectric Withstanding Voltage: 100V AC Min




*Environmental

Operating Temperature: -55℃ to +85℃.

*How to Order:

HUSB-F09-V3D-B2

Au: F>0.8u", 5:15u", 3:30u"
NO. of Contacts
Series No.



Units	mm	Scale	5:2	Drawing By	Date	益富科技有限公司	TEL: 886-3-5511680	FAX: 886-3-5511605
Tolerance Unless Otherwise Specified				ZYZ	11/17/14			
.X	~ ±0.38			Reviewed By	Date	11/17/14		
.XX	~ ±0.25			Sharon	11/17/14	Sheet	1 of 1	Title
.XXX	~ ±0.20			Approval By	Date	11/17/14	Third Angle Projection	USB 3.0 B Type Receptacle
Angle	~ ± 3°			Jason	11/17/14			Vertical Type
						Drawing No.	HUSB-F09-V3D-B2	REV
								G