





記號 MARK	設 變 內 容 MODIFICATION	日 期 DATE	修 改 DRAW	核 准 APPROVE
Δ				



LAYOUT P.C.B


NOTE:

1. MATERIAL:

- a. HOUSING:PBT GLASS FIBRE UL94 V-0 ;Black
- b. CONTACT:BRONZE T=0.25±0.02mm
- (SURFACE PLATING:Au1u"+Sn80~100u"+Ni60u")
- c. SHEEL: SPCC-SD-OILED; T=0.30±0.02mm
- (SURFACE PLATING: Cu80~100u" Ni100~120u")

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25°C~ 80°C



IF TECHNOLOGY, INC.

TEL:886-3-5511680 FAX:886-3-5511605

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE				名稱 / 料號 Title / Part No.			
.x	±0.30	繪圖 / 日期 Draw By/Date	Peter 2014/01/10	單位 Units	MM	USB A 公平版轉網 DIF22AC(前)	
.xx	±0.20	審核 / 日期 Check By/Date	Shorcon 2014/01/10	比例 Scale	1:1		顏色 Color
.xxx	±0.10	批准 / 日期 App. By/Date	Jason 2014/01/10	頁次 SHEET	1/1	角法 PROJ.	版本 REV.
.x°	±3.0°						00
.xx°	±2.0°						
.xxx°	±1.0°						