


PIN	PART NUMBER
Ø1.65	HDCJ-05E-R0D-02
Ø2.0	HDCJ-05E-R0D-00
Ø2.5	HDCJ-05E-R0D-01

SCHEMATIC



SPECIFICATION

- 1.Rating :DC 30V 0.5A
- 2.Contact resistance : $\leq 0.03\Omega$
- 3.Insulation resistance : $\geq 100M\Omega$ (DC250V)
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-20N
- 6.life test : 5,000 cycles

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			
.x	±0.30	DESIGNER BY:	Peter
.xx	±0.20	CHECK BY:	Sharon
.xxx	±0.10	APPROVED BY:	Joson
.x°	±3.0°		
.xx°	±2.0°		
.xxx°	±1.0°		
UNIT:MM	TYPE:	MODEL NO:	PAPER NO: A4
	DC POWER JACK	HDCJ-05E-R0D-0*	3:1
			1

NO.	DESCRIPTION	MATERIAL	PLATING
6	COVER	PBT	
5	HOUSING	PBT	
4	FLAT PIECE	BRASS	Sn-Plating
3	SPRING	BRONZE	Sn-Plating
2	CURVE PIECE	BRASS	Sn-Plating
1	PIN	BRASS	Ni-Plating



IF TECHNOLOGY, INC.
TEL:886-3-5511680 FAX:886-3-5511605