

REV.	ECN NO.	DATE
A	RELEASED	08/10/07
D	Modify Pin and Pin Thickness 0.15~0.20, 2.1~2.3mm	07/16/08
E	Modify the terminal material	02/08/12

NOTES:

*Material

Housing&Spacer: LCP+50%G.F., UL 94V-0 Rated, Color: Black.
Shell: Brass.
Plating: Ni(40u" Min.) Plating .
Contact: Brass.
Clip: Stainless Steel.
Plating: Au plating on contact area;
Sn(100u" Min.) plating on solder tail;
Ni(40u" Min.) underplating overall.

*Electrical Specification

Operation Voltage: 40 VAC max.
Current Rating: 0.5 Ampere per contact
Contact Resistance: 30 mΩ max.
Insulation Resistance: 100 MΩ min.
Dielectric Withstanding Voltage: 500 VAC





*Environmental

Operating Temperature: -55°C to +85°C



*How To Order

HDMI-019-R5D-0B



Au F: >0.8u" 1: 5u"
5: 15u" 3: 30u"
Number of Contacts
Series NO.



Pin Position



Reference Mount Dimension



Units	mm	Scale	1:1
Tolerance Unless Otherwise Specified			
.X	±0.38	Drawing By MAY	
.XX	±0.25		
.XXX	±0.20		
Angle	± 3°	Reviewed By SHARON	02/09/12
		Approval By JASON	02/13/12
		Date 02/08/12	
		Sheet 1 of 1	
		Third Angle Projection	
		Drawing No. HDMI-019-R5D-0B	
		REV	E



益富科技有限公司
TEL: 886-3-5511680 FAX: 886-3-5511605

High Definition Media Interface
19PIN DDP Type(Three Row, 4 Pairs)+HDMI Clip