







| 記號 | 設 變 | 日 期 | 修 改 | 核 准 |
|----|-----|-----|-----|-----|
| △ | | | | |



NOTE:

1. MATERIAL:

- a. HOUSING: PBT GLASS FIBRE UL94 V-0 ; BLACK
 - b. CONTACT: BRONZE T=0.25±0.02mm
 - (SURFACE PLATING: Au1u"+Sn80~100u"+Ni60u")
 - c. SHEEL: BRONZE T=0.30±0.02mm
 - (SURFACE PLATING: Cu80u"~100u" Ni100u"~120u")
2. ELECTRIC:
- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d. OPERATING TEMPERATURE: -55°C~85°C



UNLESS OTHERWISE SPECIFIED TOLERANCE

| ANG | TOL | DIM | TOL(1) | TOL(2) | TOL(3) | TOL(4) | TOL(5) |
|---------|------|--------|--------|--------|--------|--------|--------|
| 0~5 | ±0.1 | 0~1 | ±0.015 | ±0.02 | ±0.03 | ±0.05 | ±0.10 |
| 10~20 | ±0.2 | 1~3 | ±0.02 | ±0.03 | ±0.05 | ±0.08 | ±0.13 |
| 20~40 | ±0.3 | 3~6 | ±0.03 | ±0.05 | ±0.08 | ±0.10 | ±0.15 |
| 40~60 | ±0.5 | 6~12 | ±0.05 | ±0.08 | ±0.10 | ±0.13 | ±0.18 |
| 60~90 | ±0.8 | 12~18 | ±0.08 | ±0.10 | ±0.13 | ±0.15 | ±0.20 |
| 90~120 | ±1.0 | 18~34 | ±0.10 | ±0.13 | ±0.15 | ±0.18 | ±0.25 |
| 120~150 | ±1.5 | 34~50 | ±0.15 | ±0.18 | ±0.20 | ±0.25 | ±0.30 |
| 150~180 | ±1.8 | 50~100 | ±0.18 | ±0.20 | ±0.25 | ±0.35 | |



益 富 科 技 有 限 公 司

TEL: 886-3-5511680 FAX: 886-3-5511605

| | | | | | |
|---------------|--------------------------|-------|-----|-------------------------------|---------------------------------------|
| Draw By/Date | 彭錦學 2013.03.08 | Units | MM | 品 名 / 料 號 Title / Part NO. | USB A型插頭90°成品 (內扣) HUSB-004-RFD-12 |
| Check By/Date | Sharon Lu 2013.03.08 | 比例 | 1:1 | 材 質 Material | 顏色 Color |
| App. By/Date | Jason Chen 2013.03.08 | 頁 次 | 1/1 | 角 法 PROJ. | 版 本 REV. |
| | | | | | BLACK |
| | | | | | B |