

3D VIEW

■ SPECIFICATIONS


- Voltage Rating : 50 AC/DC
- Current Rating : 1 A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 100M Ω min
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m max

■ WAFER


- Part No. : HW10-0xx-R0S-00

Poles : 02~22


Recommended PCB Layout General tolerance \pm 0.05



CAP STOPPER



SECTION A-A



ASSEMBLED VIEW

Poles	Dimensions (mm)			Dimensions (mm)		
	A	B	C	A	B	C
2	1.00	4.00	2.45	13	12.00	15.00
3	2.00	5.00	3.45	14	13.00	16.00
4	3.00	6.00	4.45	15	14.00	17.00
5	4.00	7.00	5.45	16	15.00	18.00
6	5.00	8.00	6.45	17	16.00	19.00
7	6.00	9.00	7.45	18	17.00	20.00
8	7.00	10.00	8.45	19	18.00	21.00
9	8.00	11.00	9.45	20	19.00	22.00
10	9.00	12.00	10.45	21	20.00	23.00
11	10.00	13.00	11.45	22	21.00	24.00
12	11.00	14.00	12.45			



益富科技有限公司
TEL:886-3-5511680 FAX:886-3-5511605

PART NO HW10-0xx-R0S-00

1.00mm WIRE TO BOARD CONNECTOR, SMT & Right Angle

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	\pm 0.30	Δ	增加無面材料；合併圖面	金飛	2010/11/01	Δ	增加電鍍規格QD及修改用材料	黃廣珍	2014/03/04
CHECKED BY	PROJ	VER NO.	\pm 0.20	Δ	刪減多餘尺寸	周美麗	2011/10/20	Δ	外觀修正增加模數與穴位缺口	吳弘文	2014/11/17
周家慶		Q19	\pm 0.10	Δ	新增LCP材質	王城賢	2012/05/29	Δ	無面代碼"R"刪除,與旧重覆	鄭小嬌	2015/10/26
DRAWN BY	DATE	SIZE	ANGLE	Δ	新增阻焊填及修改原阻焊填為IP	林謙豪	2012/06/07				
鄭小嬌	2015/10/26	A4	\pm 1 $^{\circ}$	Δ	修正編碼選項	吳弘文	2013/02/25				
			\pm	Δ	修改接地片位置	黃廣珍	2013/04/19				
			1/1	Δ	增列額定電壓	吳弘文	2013/08/08				

Conforms to The RoHS Instruction