



■ SPECIFICATIONS

- Voltage Rating : 100V AC/DC
- Current Rating : 2A AC/DC
- Withstanding Voltage : 800V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact resistance : 20m Ω max

■ WAFER

- Poles : 2-16
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-0
- Q' ty : 1,000 pcs/Bag

Poles	Part No.	Dimensions (mm)		
		A	B	C
2	HW20-002-R0D-00	2.00	6.00	5.00
3	HW20-003-R0D-00	4.00	8.00	7.00
4	HW20-004-R0D-00	6.00	10.00	9.00
5	HW20-005-R0D-00	8.00	12.00	11.00
6	HW20-006-R0D-00	10.00	14.00	13.00
7	HW20-007-R0D-00	12.00	16.00	15.00
8	HW20-008-R0D-00	14.00	18.00	17.00
9	HW20-009-R0D-00	16.00	20.00	19.00
10	HW20-010-R0D-00	18.00	22.00	21.00
11	HW20-011-R0D-00	20.00	24.00	23.00
12	HW20-012-R0D-00	22.00	26.00	25.00
13	HW20-013-R0D-00	24.00	28.00	27.00
14	HW20-014-R0D-00	26.00	30.00	29.00
15	HW20-015-R0D-00	28.00	32.00	31.00
16	HW20-016-R0D-00	30.00	34.00	33.00



益富科技有限公司
TEL:886-3-5511680 FAX:886-3-5511605

PART NO HW20-0xx-R0D-00

2.00mm Crimp Style Connectors Wafer

APPROVED BY

林陳鏢

SCALE

4:1

UNIT

mm

TOLERANCE

.0 ±0.3

.00 ±0.2

.000 ±0.1

ALL ±

ANGLE

0° ±

.0° ±

LTR

ECR

REVISION RECORD

200506-012

DATE

2005/06/09

CHECKED BY

曲智浩

PROJ



VER NO.

a2

DRAWN BY

龔志紅

DATE

2005/06/08

SIZE

A4