

Schematic




SPECIFICATIONS:

CONTACT RATING : 6 AMPS @ 120 V AC or 28 V DC.
 3AMPS @250 V AC or 0.4 AMPS @ 20V AC or DC
 ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.
 MECHANICAL LIFE: 30,000 make-and-break cycles.
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.
 100 mA, for both silver and gold plated contacts.
 INSULATION RESISTANCE : 1,000 MΩ min.
 DIELETRIC STRENGTH : 1,000 V RMS @ sea level.
 OPERATING TEMPERATURE : -30°C to 130 °C




MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).
 ACTUATOR : Nylon.
 BUSHING : Brass, nickel plated.
 HOUSING : Stainless steel.
 TERMINAL/CONTACT : Brass, with silver or gold plated.
 or gold over silver
 SWITCH SUPPORT : Brass, tin plated.

P.C. MOUNTING



Model NO.	TYPE		
	ON	NONE	ON
HSW-DS-13C	ON	NONE	ON
HSW-DS-14C	ON	OFF	ON
Tem. Comm.	2-1	OPEN	2-3

 <div>益富科技有限公司</div> <div>TEL:886-3-5511680</div> <div>FAX:886-3-5511605</div>	比例 SCALE	N/A	品名 TITLE		SLIDE SWITCH			
	單位 DIMENSION	m m	型號 MODEL		HSW-DS-13C			
	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE		繪 圖 DRAWN		HSH		核 准 APPROVED	HSH
	UP TO 10	± 0.3	 		版 次 REVISION	A	日 期 DATE	2015/09/30
	ABOVE 10 TO 100	± 0.5						
ABOVE 100	± 0.8							
ANGULAR DIMENSIONS	± 5°							