

SPECIFICATIONS:

CONTACT RATING : 6 AMPS @ 120 V AC or 28 V DC.

3AMPS @250 V AC or 0.4 AMPS @ 20V AC or DC

ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.

MECHANICAL LIFE: 30,000 make-and-break cycles.

CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.


100 mA, for both silver and gold plated contacts.

INSULATION RESISTANCE : 1,000 MΩ min.



DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.

OPERATING TEMPERATURE : -30°C to 130 °C

P.C. MOUNTING



Schematic



MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).

ACTUATOR : Nylon.

BUSHING : Brass, nickel plated.

HOUSING : Stainless steel.

TERMINAL/CONTACT : Brass, with silver or gold plated.

or gold over silver

SWITCH SUPPORT : Brass, tin plated.

Model No.	TYPE		
HSW-DS-13P	ON	NONE	ON
HSW-DS-13P-3	ON	OFF	ON
Tem. Comm.	2-1	OPEN	2-3



益富科技有限公司

TEL:886-3-5511680

FAX:886-3-5511605

比例 SCALE N/A

單位 DIMENSION m m

DO NOT SCALE DRAWING
TOLERANCES UNLESS OTHERWISE

UP TO 10 ±0.3

ABOVE 10 TO 100 ±0.5

ABOVE 100 ±0.8

ANGULAR DIMENSIONS ±5°

品名 TITLE

Slide Switch

型號 MODEL

HSW-DS-13P-G7.35

繪圖
DRAWN

HSH

核准
APPROVED

JASON



版次
REVISION

A

日期
DATE

2015/09/30