




Specifications  
 Current Rating: 3.0 Amps  
 Voltage Rating: 100V AC/DC  
 Contact Resistance: 10m Ohm. Max.  
 Insulator Resistance: 5,000M Ohm. Min.  
 Withstanding Voltage: 1,000V AC for One Minute  
 Operating Temperature Range:  $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$   
 Material and Plated  
 Insulator: High Temp. Plastic (PPS UL94V-0)  
 Insulator Color: Black  
 Contact: Brass  
 Plated: Gold Plated, Tin Plated

Part Number : HH54-140-VFD-R0

No. of Position



PCB LAYOUT

Dimension:

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
2	5.08	2.54	12	30.48	27.94	22	55.88	53.34	32	81.28	78.74
3	7.62	5.08	13	33.02	30.48	23	58.42	55.88	33	83.82	81.28
4	10.16	7.62	14	35.56	33.02	24	60.96	58.42	34	86.36	83.82
5	12.70	10.16	15	38.10	35.56	25	63.50	60.96	35	88.90	86.36
6	15.24	12.70	16	40.64	38.10	26	66.04	63.50	36	91.44	88.90
7	17.78	15.24	17	43.18	40.64	27	68.58	66.04	37	93.98	91.44
8	20.32	17.78	18	45.72	43.18	28	71.12	68.58	38	96.52	93.98
9	22.86	20.32	19	48.26	45.72	29	73.66	71.12	39	99.06	96.52
10	25.40	22.86	20	50.80	48.26	30	76.20	73.66	40	101.60	99.06
11	27.94	25.40	21	53.34	50.80	31	78.74	76.20			



益富科技有限公司

TEL: 886-3-5511680 FAX: 886-3-5511605

DRAWING No.

HH54-1xx-VFD-R0

SCALE

NONE

APPROVED BY

Jason

CHECKED BY

Jason

DRAWING BY

Sharon

REV.

A0

UNLESS OTHERWISE  
SPECIFIED  
TOLERANCES ARE  
.X ±0.20  
.XX  
ANG.

UNIT  
mm



NO. REV.

A0 NEW RELEASE

REVISIONS

CHK

DATE