









NOTE:
1.OPEN/SHORT TEST:100%;
2.CONDUCTOR RESISTANCE:5Ω;
3.INSULATION RESISTANCE:20MΩ;
4.HI-POT TEST:300V/DC;
5.ALL MATERIALS MUST ACCORD WITH RoHS;



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

包装说明:
1. 将检验好的成品;SMT朝下放入载带底部;每卷装800PCS产品,8000PCS/箱;具体如图一所示
2. 将包装好的产品;每盘必需贴上内标签;具体如图二所示
3. 将贴好内标签的产品每10盘叠一层装入防水袋中并加一包干燥剂;装好后将防水袋封好;具体如图三图四所示
4. 先将1pcs平卡放入纸箱底部;然后将装好产品的防水袋装入纸箱中;防水袋热封封口,封口面需朝上;并将4PCS三角套分别装入4个角;如图五所示
5. 装好后将1pcs平卡放入纸箱最上面并封好纸箱及贴好相关标签;具体如图六所示:
(产品包装的标签,如客户有要求,请按客户要求包装出货)
6. 载带前面留30PCS空格,后面留20PCS空格
7. COVER与CARRY剥离力:50-125g,速度:300mm/分钟左右,剥离角度:165°-180°



备注:

1. 材质:
1.1 胶芯: LCP+30%G.F UL94V-0
1.2 端子: COPPER ALLOY;
1.3 外壳: SUS304, T=0.30mm; 表面镀镍100μ"
1.4 护板: 不锈钢, T=0.15mm;
2. 主要特性:
2.1 额定电流: 3A MIN FOR VBUS, 0.25A MIN FOR OTHER.
2.2 接触阻抗: 40mΩ MAX
2.3 绝缘阻抗: 100MΩ MIN 250V DC
2.4 耐压测试: 100V AC
2.5 沾锡性: 温度250±5℃, 时间5±0.5s
2.6 整体插入力: 2.00kgf MAX
整体拔出力: 0.80kgf MIN
2.7 使用寿命: 10000 次
2.8 工作温度: -55℃~+85℃

HUSC-024-RFS-90

PACKING OPTION
Blank=TAPE & Reel Packing

CANTACT PLATING
F=G/F
3=30u

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

TOLERANCE UNIT(mm)		APPROVALS	DATE	益富科技有限公司 TEL:886-3-5511680 FAX:886-3-5511605			
X.	±0.30	DRAWN WINKI	06/20/2016	TITLE USB 3.1 C FEMALE(雙排貼/24PIN)			
X.X	±0.25	CHECKED JOHNSON	06/20/2016				
X.XX	±0.15	APPROVED JOHNSON	06/20/2016				
X.XXX	±0.08	UNLESS OTHERWISE SPECIFIED		SCALE N.A.	PART NO. HUSC-024-RxS-90	DRAWING NO. T50E7322XXXX0ET A	REV. A
ANGULAR	±2°			SHEET 1 OF 1	CUSTOMER PART NO.		
		UNIT MM		CUSTOMER CODE			